



TYREE NZ LIMITED

NZ.B.N. 9429039137081
NZ.C.N. 498479
23a Timberly Road Mangere
Auckland 2022
PO Box 132 247,
Sylvia Park, Auckland 1644
PHONE +64 9 573 1990
EMAIL: info@tyree.nz

PRODUCT SPECIFICATION



1. PRODUCT CODE BED3G05

2. DESCRIPTION 3 Core Flat 7/0.5 (1.5mmsq nom.). P.A.C.W.
Non Migratory P.V.C. Insulated and Sheathed.
Building cable 450/750 Volt to AS/NZS 5000.2.
Oxygen Free Copper. RoHS compliant.

3. CONSTRUCTION

- 3.1 CONDUCTOR:** 7 strands of 0.5mm nom. Plain Annealed Copper to
AS/NZS 1125 Class 2.
Max. D.C. resistance at 20C: 13.6 ohms / km
- 3.2 INSULATION:** Coloured Non Migratory V90 P.V.C. to AS/NZS 3808.
Nominal Diameter: 2.7 mm
Nominal Wall Thickness: 0.6 mm
- 3.3 CORE COLOURS:** 1. Red
2. White
3. Blue
Laid parallel
- 3.4 SHEATH:** Coloured Non Migratory 3V90 P.V.C. to AS/NZS 3808.
Flat configuration
Nominal Dimensions: 4.6 x 9.9 mm
Nominal Wall Thickness: 0.9 mm