



TYREE NZ LIMITED

NZ.B.N. 9429039137081
NZ.C.N. 498479
23a Timberly Road
Mangere
Auckland 2022
PO Box 132 247,
Sylvia Park,
Auckland 1644
PHONE +64 9 573 1990
EMAIL: info@tyree.nz

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** **ABC128703**
- 2. DESCRIPTION** **252/0.32 (20.26 mmsq – 4 B&S)**
Plain Copper Wire Automotive Battery cable.
60Volt V90 PVC. Not for Mains Connection.
Oxygen Free Copper. RoHS compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** **252** strands of 0.32 mm Plain Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.
Max. D.C. resistance at 20C: 0.9 ohms / km
TYPICAL conductor diameter: 5.95 mm
- 3.2 INSULATION:** Coloured P.V.C. type V90 to AS/NZS3808
Nominal Diameter: 8.3 mm
Nominal Wall Thickness: 1.1 mm
- 3.3 SHEATH COLOURS:** Black or Red
- 4. REFERENCE STANDARDS**
- 4.1 AS/NZS3808** **PVC** compound type.
- 4.2 AS/NZS1125** Conductor Tolerances
- 4.3 AS/NZS1574** Copper Type
- 4.4 SAE J1127** Minimum cross-section conductor area and Minimum Wall Thickness