



TYREE NZ LIMITED

NZ.B.N. 9429039137081
NZ.C.N. 498479
23a Timberly Road
Mangere
Auckland 2022
O Box 132 247,
Sylvia Park,
Auckland 1644
PHONE +64 9 573 1990
EMAIL: info@tyree.nz

PRODUCT SPECIFICATION



1. PRODUCT CODE **ATC7903**

2. DESCRIPTION 7 Core 8/.32 (0.64sqmm)P.C.W. V90 PVC insulated.
5V90 PVC sheathed trailer cable.
Extra Low Voltage. Not for Mains connection.
Oxygen free copper. RoHS compliant PVC.

3. CONSTRUCTION

3.1 CONDUCTOR: 7 strands of 0.32 mm Annealed Copper to
AS/NZS 1125 drawn from Class 102
copper to AS/NZS 1574.
Max.D.C. resistance at 20C: 29.9 ohms /km

3.2 INSULATION: Coloured V90 PVC to AS/NZS 3808.
Nominal Diameter: 2.0 mm
Nominal Wall Thickness: 0.4 mm

3.3 COLOURS 7 Cores.
1. Brown 2. Red 3. Green 4. White 5. Yellow
6.Black 7. Blue
Sheath: Black

3.4 SHEATH Coloured P.V.C. type 5V90 to AS/NZS 3808.
Nominal Diameter: 7.25 mm
Nominal Wall Thickness: 0.6mm