



TYREE NZ LIMITED

NZ.B.N. 9429039137081
NZ.C.N. 498479
23a Timberly Road
Mangere
Auckland 2022
O Box 132 247,
Sylvia Park,
Auckland 1644
PHONE +64 9 573 1990
EMAIL: info@tyree.nz

PRODUCT SPECIFICATION



- 1. PRODUCT CODE:** DMC41402
- 2. DESCRIPTION:** 4 core 14/0.2 PCW (0.4mmsq) V75 Insulated Aluminium / Polyester tape screened including a 7/0.2 tinned drain wire. V75c PVC Sheathed.
Extra Low Voltage use, not for mains connection.
AUSTEL approval A93/CA/0122
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 14 strands of 0.2mm nom. Annealed Copper to AS1125 drawn from Class 110A copper to AS1574.
Max. D.C. resistance at 20C : 45.0 ohms / klm
- 3.2 INSULATION:** Coloured P.V.C to AS3808 type V75.
Nominal Diameter : 1.45 mm
Nominal Wall Thickness : 0.26 mm
- 3.3 LAYUP:** 4 cores twisted.
1. Red
2. Blue
3. Green
4. Yellow
- 3.4 SCREEN:** Aluminium / Polyester tape screen in contact along its length with a 7/2 TACW drain wire.
- 3.5 SHEATH:** Coloured P.V.C. to AS3808 type 4V75
Nominal Diameter : 5.3 mm
Nominal Wall Thickness : 0.76 mm