



## **TYCAB AUSTRALIA PTY LTD**

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

[www.tycab.com.au](http://www.tycab.com.au)

### **PRODUCT SPECIFICATION**

- 1. PRODUCT CODE** FMC04/1.5
- 2. DESCRIPTION** 4 Core 30/.25 (1.5 mm sq ,15amp) .P.C.W. V90 PVC insulated.  
5V90 P.V.C. sheathed. Flexible cord.  
250/440v to AS/NZS 3191 .  
RoHS Compliant .
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 30 strands of 0.25 mm Plain Annealed Copper to  
AS/NZS 1125 drawn from Class 110 copper to AS/NZS 1574.  
Max. D.C. resistance at 20C : 13.3 ohms / km
- 3.2 INSULATION :** Coloured V90 PVC to AS/NZS 3808  
Nominal Diameter : 3.0 mm Nom. Wall Thickness: 0.7 mm
- 3.3 LAY UP** 4 Cores laid up .  
1. Brown 2. Lt Blue. 3.White 4. Lt Green/ Yellow
- 3.4 SHEATH** Coloured P.V.C. type 5V90 to AS/NZS 3808.  
Nominal Diameter : 9.2 mm Nom. Wall Thickness : 1.0 mm
- 3.5 IDENTIFICATION** Indented into sheath at intervals not exceeding 500mm