




## TYREE NZ LIMITED

NZ.B.N. 9429039137081  
NZ.C.N. 498479  
23a Timberly Road  
Mangere  
Auckland 2022  
O Box 132 247,  
Sylvia Park,  
Auckland 1644  
PHONE +64 9 573 1990  
EMAIL: info@tyree.nz

### PRODUCT SPECIFICATION



**1. PRODUCT CODE:** DMC6702

**2. DESCRIPTION:** 6 core 7/0.2 PCW  
V75 Insulated Aluminium / Polyester tape screened including a  
7/0.2 tinned drain wire. V75C PVC Sheathed.  
AUSTEL A93/CA/0123  
Extra Low Voltage use, not for mains connection.  
Oxygen Free Copper. RoHS Compliant PVC.

### 3. CONSTRUCTION

**3.1 CONDUCTOR:** 7 strands of 0.2mm nom. Annealed Copper to AS/NZS1125  
drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 89.5 ohms / km

**3.2 INSULATION:** Coloured P.V.C to AS/NZS3808 type V75.

Nominal Diameter: 1.15 mm

Nominal Wall Thickness: 0.26 mm

**3.3 LAYUP:** 6 cores twisted.

1. Red	2. Blue
3. Green	4. Yellow
5. White	6. Black

**3.4 SCREEN:** Aluminium / Polyester tape screen in contact along its length  
with a 7/2 TACW drain wire.

**3.5 SHEATH:** Coloured P.V.C. to AS/NZS3808 type 4V75

Nominal Diameter: 5.25 mm

Nominal Wall Thickness: 0.76 mm