



TYREE NZ LIMITED

NZ.B.N. 9429039137081
NZ.C.N. 498479
23a Timberly Road
Mangere
Auckland 2022
O Box 132 247,
Sylvia Park,
Auckland 1644
PHONE +64 9 573 1990
EMAIL: info@tyree.nz

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** AFC22603

- 2. DESCRIPTION** 2 Core Parallel Webbed (Figure 8) 23/.32 (1.84mmsq) P.A.C.W, V90 PVC insulated. L.D.P.E insulated.
Extra low voltage automotive cable, Not for mains outlet connection.

- 3. CONSTRUCTION**
 - 3.1 CONDUCTOR:** 23 strands of 0.32 mm Plain Annealed Copper to AS1125 drawn from Class 102 copper to AS1574.

Max. DC Resistance at 20C : 10.1 ohms/km

 - 3.2 INSULATION:** Coloured V90 PVC to AS3808.
Parallel Webbed (Figure 8) construction.

Nominal Diameter: 3.1 x 6.7mm
Nominal Wall Thickness: 0.6mm

 - 3.3 SHEATH COLOURS:** Red with a Black stripe
Black with a White stripe
Blue with a White stripe
Other combinations also available
Polarity identification by coloured stripe.