



## **TYREE NZ LIMITED**

NZ.B.N. 9429039137081  
NZ.C.N. 498479  
23a Timberly Road  
Mangere  
Auckland 2022  
O Box 132 247,  
Sylvia Park,  
Auckland 1644  
PHONE +64 9 573 1990  
EMAIL: info@tyree.nz

### **PRODUCT SPECIFICATION**



- 1. PRODUCT CODE**     **ATC57032**
- 2. DESCRIPTION**     5 Core 7/.32 (0.56sqmm). Plain Copper Wire  
V90 P.V.C. Insulated and 5V90 P.V.C. Sheathed Trailer cable.  
Extra Low Voltage. Not for Mains connection.  
RoHS compliant P.V.C.  
Oxygen Free Copper.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:**     7 strands of 0.32mm nom. Annealed Copper to  
AS/NZS 1125 drawn from Class 102 copper to  
AS/NZS 1574.  
Max. D.C. resistance at 20C: 33.0 ohms / km
- 3.2 INSULATION:**     Coloured V90 PVC to AS/NZS 3808.  
Nominal Diameter: 1.8 mm  
Nominal Wall Thickness: 0.4 mm
- 3.3 LAY UP**             5 Cores.  
1. Brown 2. Red 3. Green 4. White 5. Yellow  
Sheath: Black
- 3.4 SHEATH**             Coloured P.V.C. type 5V90 to AS/NZS 3808.  
Nominal Diameter: 6.0 mm  
Nominal Wall Thickness: 0.6mm