



TYREE NZ LIMITED

NZ.B.N. 9429039137081
NZ.C.N. 498479
23a Timberly Road
Mangere
Auckland 2022
O Box 132 247,
Sylvia Park,
Auckland 1644
PHONE +64 9 573 1990
EMAIL: info@tyree.nz

PRODUCT SPECIFICATION



1. PRODUCT CODE AWC24103

2. DESCRIPTION 2 Core Flat Twin Sheathed 36/.32 (2.89mmsq) P.A.C.W.
V90 PVC insulated & 5V90 PVC Sheathed.
60 v dc AUTOMOTIVE CABLE
Not for Mains GPO Connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 36 strands of 0.32mm Plain Annealed Copper to
AS1125 drawn from Class 110A copper to AS1574.
Max. D.C. resistance at 20C : 6.4 ohms/klm

3.2 INSULATION: Coloured V90 P.V.C to AS 3808.

Nominal Diameter: 3.0mm
Nominal Wall Thickness: 0.4mm

3.3 CORE COLOURS: 1. Black 2. Red
Laid Parallel

3.4 SHEATH: Black
Coloured 5V90 to AS3808 Flat Configuration

Nominal Dimensions: 4.50mm x 7.40mm
Nominal Wall Thickness: 0.7mm