



## TYREE NZ LIMITED

NZ.B.N. 9429039137081  
NZ.C.N. 498479  
23a Timberly Road  
Mangere  
Auckland 2022  
O Box 132 247,  
Sylvia Park,  
Auckland 1644  
PHONE +64 9 573 1990  
EMAIL: info@tyree.nz

### PRODUCT SPECIFICATION



**1. PRODUCT CODE:** AWC21603

**2. DESCRIPTION** 2 Core Flat Twin Sheathed 14/.32 (1.13 mm sq). P.A.C.W.  
V90 Insulated & 5V90 Sheathed Automotive.  
Extra Low Voltage, Not for Mains Connection.

#### 3. CONSTRUCTION

**3.1 CONDUCTOR:** 14 strands of 0.32mm Plain Annealed Copper to AS/NZS1125  
drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 16.5 ohms / km

**3.2 INSULATION:** Coloured V90 P.V.C. to AS/NZS3808.

Nominal Diameter: 2.15 mm  
Nominal Wall Thickness: 0.4 mm

**3.3 CORE COLOURS:** 1. Red  
2. Black  
Laid parallel

**3.4 SHEATH:** Black  
Coloured 5V90 to AS/NZS3808  
Flat configuration

Nominal Dimensions: 3.3 x 5.5 mm  
Nominal Wall Thickness: 0.6 mm