

GBT506 SEAMLESS SLIMLINE

TRI-COLOUR LINKABLE LED BATTEN




FEATURES

- Polycarbonate body
- Double insulated PC housing
- Opal polycarbonate diffuser
- Built-in constant current LED driver
- Mounting bracket and connector (straight and 10cm flexible) included
- Select colour temperature with DIP switch
- LED lifespan: 50000 hours @ L70, Ta 25°C
- Ta: 0°C to +25°C



DIMENSIONS



280 TC: 280 | 540TC: 540 | 840 TC: 840 | 1140 TC:1140 | 1440 TC: 1440

Unit: mm

Mixed connections **maximum 240W**

GBT506/280 TC	1 2 3 4...	55pcs
GBT506/540 TC	1 2 3 4...	25pcs
GBT506/840 TC	1 2 3 4...	17pcs
GBT506/1140 TC	1 2 3 4...	12pcs
GBT506/1440 TC	1 2 3 4...	10pcs

ACCESSORIES

- GBT506/32CM LINK (L 320 mm)
- GBT506/76CM LINK (L 760 mm)

TECHNICAL SPECIFICATIONS

MODEL NO.	INPUT VOLTAGE (V)	POWER (W)	LUMEN (lm)	COLOUR TEMPERATURE (K)	CRI	BEAM ANGLE (°)	FITTING COLOUR	CARTON QUANTITY
GBT506/280 TC	230	4	300/380/300	3000/4000/5500	>80	105	White	30
GBT506/540 TC		9	750/800/750					
GBT506/840 TC		13	1050/1200/1050					
GBT506/1140 TC		18	1550/1600/1550					20
GBT506/1440 TC		22	1800/2000/1800					

Specifications above are for reference only and may vary without prior notice