

MAXI BRICK II GLW407/8

IP65 RECESSED LED BRICK LIGHT



GLW407

GLW408




FEATURES

- Die-cast aluminium body and stainless steel face cover
- Powder coated finish
- Opal polycarbonate diffuser
- IP68 PG9 PVC cable gland
- Stainless steel allen screws
- Installation ABS mounting sleeve included
- Pre-wired 3 core rubber flex
- Built-in constant current LED driver
- LED lifespan: 50000 hours @ L70, Ta 25°C
- Ta: -20°C to +40°C



DIMENSIONS





INSTALLATION

HIGH VOLTAGE TYPE



ABS MOUNTING SLEEVE

MOUNTING SLEEVE



Unit: mm

- The mounting box and support plates (A1/A2) are used during the installation process to prevent the sleeve distorting
- The support plates (A1/A2) must be removed before installation

TECHNICAL SPECIFICATIONS

MODEL NO.	INPUT VOLTAGE (V)	POWER (W)	LUMEN (lm)	COLOUR TEMPERATURE (K)	CRI	FITTING COLOUR	CARTON QUANTITY
GLW407 CW	230	6.5	85	4000	>80	Stainless steel	4
GLW408 CW	230	6.5	85	4000	>80	Stainless steel	4