

GDY285

DAYTONA

CIRCULAR LED BULKHEAD LIGHT



FEATURES

- Polycarbonate body
- Opal polycarbonate diffuser
- Constant current LED driver fitted
- Select colour temperature with DIP switch
- Power factor: 0.9
- Colour matching 6 MacAdam steps
- LED lifespan: 50000 hours @ L70 B10, Ta 25°C
- Ta: -20°C to +50°C


ON 1 2 3 Power Selectable	POWER	PIN1	PIN2	PIN3
	7.5W	OFF	OFF	OFF
	9W	ON	OFF	OFF
	10.5W	OFF	ON	OFF
	12W	ON	ON	OFF
	13.5W	OFF	OFF	ON
	15W	ON	OFF	ON
	16.5W	OFF	ON	ON
	18W	ON	ON	ON



Emergency

- Intelligent automatic recharging function
- Compliant to AS/NZS 2293
- Constant current mode
- 3 hour emergency operation
- LED charge status display
- Deep discharge protection
- Test switch with self-test function
- LiFePO4 battery
- Ta: 0°C to +40°C

DIMENSIONS



OPTIONS

- MICROWAVE MOTION SENSOR: GMS804



TECHNICAL SPECIFICATIONS

MODEL NO.	INPUT VOLTAGE (V)	POWER (W)	OUTPUT CURRENT (mA)	LUMEN (lm)	COLOUR TEMPERATURE (K)	CRI	BEAM ANGLE (°)	FITTING COLOUR	CARTON QUANTITY
GDY285 TC	230	Max18	450	1800	3000/4000/6000	>80	120	White	10
GDY285 TC EM	230	Max18(2.3)*	450	1800(340)*	3000/4000/6000	>80	120	White	10

*When running on EM backup wattage is 2.3W and lumen 340lm

Specifications above are for reference only and may vary without prior notice